

Fuel dispenser

SK10 Series

Features:

- Customer friendly operation
- Trustable highly precise metrology equipment
- High performance for electronic parts
- High quality explosion-proof motor with strong ability against power fluctuation
- Specially designed filtering systems with build-in re-cleanable filter
- Flexible fuel application for gasoline, diesel, and kerosene etc.
- Works well in harsh conditions, like extremely cold, hot, humid, and sand-stormy environment



Beijing Sanki Petroleum Technology Co., Ltd
 № 16, 2nd Kechuang Str., Economic-Technological Development Area, Beijing, China, 100023
 Tel: +86 10 67892321 Fax: +86 10 67892321
 E-mail: business@sankichina.com <http://www.sankichina.com>

Technical specification:

| | |
|------------------------------------|--|
| Accuracy for the unit | ±0.25% |
| Flow rate | 50L/min |
| Ambient temperature | -25°C ~ +55°C; or -45°C ~ +55°C |
| Relative humidity | 20% - 95% |
| Unit noise rate | <70dB (A); |
| Inlet vacuum rate for suction pump | ≥ 54kPa |
| Communication | With RS 485 port, or current loop |
| Power supply | AC 220V(-15%~+10%); (50/60±1)Hz AC 380V(-15%~+10%); (50/60±1)Hz |
| Digit of sale | 0.00~99999.99 |
| Digit of volume | 0.00~9999.99 |
| Digit of unit price | 0.00~999.99 |
| Totalizer of sale | 0~99999999.99 |
| Totalizer of volume | 0~9999999.99 |

Basic Configurations:

- Main board, power board, display board, keypad, control board, pump, motor, flow meter, solenoid valve, electromagnetic counter, filter, nozzle, hose, sight glass

Optional Configuration:

- Stage II Vapor Recovery, card reader payment, double swivel, printer, heater for ultra low temperature, breakaway coupling, emergency shutoff button, shutoff valve for remote dispenser, standard electronics interface to POS and automation fuel management system

Model Range :

| Model | Pump unit | Nozzle | Oil | Package Size (mm) | Gross Weight (kg) |
|------------|------------------|--------|-----|-------------------|-------------------|
| SK10ZF111B | suction pump | 1 | 1 | 768*546*1570 | 130 |
| SK10QF111B | Submersible pump | 1 | 1 | 768*546*1570 | 104 |